

SIGIL CLACK

WATERBASED SEALANT FOR LAMINATES OR FLOATING T&G FLOORS

Singlecomponent fluid sealant for treating the joints of floating floors, laminate or T&G type, also prefinished; ideal for elements suitable to be replaced. Sigil Clack is particularly advised in case of damp environments like kitchens, bathrooms, because it creates a water-proof barrier avoiding the joints to expand. Sigil Clack is easy to apply thanks to the handy pouring lip on the bottle, it assures fast drying and very easy cleaning.



Technical data

Physical characteristics (20°C – 60% R.H.)			
Appearance	White paste	Specific gravity	1,05 g/cm ³
Viscosity (Brookfield 25°C)	10.000 mPa.s		
Times (20°C – 60% R.H.)			
Open time	5-10'	Walk on	12-24 hours (See notes)
Time for setting	1-2 hours	Complete hardening	24-48 hours
Technical characteristics			
Yield	50 linear mt with 500ml	Application temp.	> + 10°C
Elongation to break	> 200% (estimated value)		
Storage and labeling			
Storage in original packag. closed at T >+ 10°C	12 months KEEP AWAY FROM FROST	Symbols of risk	NONE
Tools cleaning	when still fresh it can be cleaned just with water, when dry use acetone		
Packaging	Bottles of 500 ml with pouring lip		

Application

Take care the surfaces to be treated are well clean and dry.

Cut the ending lip of the bottle with the needed section. Apply Sigil Clack on the male element and immediately proceed to coupling. Once the element is inserted make a weak pressure to improve a continuous seal. For remove exceeding product proceed as follow:

Cleaning after drying: when the sealant is dry remove it by finger or by suitable tool be careful to not scratch or damage the surface. Sigil Clack does not adheres to prefinished coats and it can be easily peeled out without using solvents.

Cleaning immediately: when the sealant is still fresh, take it away by sponge or slightly damp cloth. This operation is advised when laying prefinished rounded edges elements.

Cleaning after laying.

When it is possible to walk on the floor, clean the surface using the specific cleaner Ready-Pro removing halos and dirt.

Notes

- ✓ When dry, Sigil Clack becomes transparent.
- ✓ Even if the layed elements are set after few hours, we advice to wait at least 12-24 hours before to walk on. During this period the mechanical features grown up and local stress could affect the continuity of sealing
- ✓ In any case follow installation guidelines given by the floor manufacturer

Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on labels and consult the safety data sheet before using the product.

Disposal of waste

Dispose unused product and empty packages according to local in force regulations.

WARNING: The information reported in present technical data sheet are for guidance only and they do not hold our responsibility; the environmental conditions and the employ modalities are out of our control. We advice to check that the product fits for the work to be done.

REV.5 30-03-2011. Current Technical Data Sheet replaces the previous one.



TOVER S.R.L.
Via Rosa Luxembourg 2/A
10093 COLLEGNO (TO)
P.IVA 07783540011
R.E.A. n°920259
Tel.: +39-011/7792823
Fax: +39-011/7792749
www.tover.com
e-mail: info@tover.com
Made in Italy

